


THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF L-COM, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF L-COM, INC. IS PROHIBITED.

RoHS Compliant ✓

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	5/24/11	D.FRISIELLO
B	ECN 6753: REVISED MOUNTING HOLE PATTERN	3/26/13	D.FRISIELLO



MATERIAL

PANEL : SPCC BLACK POWDER PAINTING COAT FINISH
 SHIELDED CASE : BRASS WITH NICKEL PLATED
 JACK HOUSING : ENGINEERING THERMOPLASTIC FLAMMABILITY RATING UL 94V-0
 SPRING WIRE : PHOSPHOR BRONZE T=0.35MM , 6U" GOLD PLATING OVER NICKEL IN CONTACT.
 TIN PLATING OVER NICKEL UNDERCOAT IN SOLDER AREA.
 IDC PLASTIC : POLYCARBONATE RESIN HIGH-IMPACT UL94V-0 THERMOPLASTIC
 IDC CONTACT : PHOSPHOR BRONZE C5191R-H, T=0.4MM, 100U" TIN OVER 50U" NICKEL UNDERCOAT
 SCREW : CROSS RECESSED HEXAGON HEAD M5 X 12MM BLACK PAINTED

PHYSICAL CHARACTERISTICS

SUITABLE IMPACT TOOL : 110 STYLE PUNCH DOWN TOOL.
 INSERTION LIFE : 750 MATING CYCLES WITH FCC COMPLIANT RJ-45 PLUG.
 CONTACT FORCE : 100 GRAMS WITH FCC COMPLIANT RJ-45 PLUG.
 PLUG RETENTION FORCE : 11 LBF MIN.
 DURABILITY : 200 TERMINATION CYCLES.
 CONTACT COMPATIBILITY : ACCOMMODATES 22 TO 24 AWG SOLID.
 OPERATING TEMPERATURE RANGE : -10°C TO 60°C.
 STORAGE TEMPERATURE RANGE : -40°C TO 68°C.
 HUMIDITY : 10%-90%RH.

ELECTRICAL

INSULATION RESISTANCE : 500 MΩ.
 DIELECTRIC WITHSTANDING VOLTAGE : 1000 V AC.
 DC CURRENT RATING : 1.5 Amps.
 DC RESISTANCE : 0.1Ω.
 CONTACT RESISTANCE : 20mΩ.


NOTE

B : DO NOT INSERT RJ-11 6P PLUG.



CAT 5e
 56Y4
 E145249

ACCORDING TO: ANSI/TIA-568-C.2
 REQUIREMENTS
 C5e CONNECTING HARDWARE



ENCLOSURE

NYLON CABLE TIE X 24 PCS
 SCREW X 4 PCS
 INSTRUCTION X 1PC

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN MM	APPROVALS	DATE	45 BEECHWOOD DRIVE NORTH ANDOVER, MA 01845
	DRAWN BY D.FRISIELLO	5/24/11	
	CHECKED BY M.MARTINEZ	5/24/11	
	APPROVED BY M.MARTINEZ	5/24/11	
PROJECTION 	CONFIGURATION DETAILS OF UNDIMENSIONED FEATURES MAY VARY	CATEGORY RACK PANELS	
	COLOR VARIATIONS MAY OCCUR	PRODUCT DESCRIPTION .875"X19"PNL CAT5E 24PT SHLD	
	SIZE A	FSCM NO. 43321	DWG. NO. DCP110C5E-24S
SCALE: NONE		CAD FILE: DCP110C5E-24S.SLDDRW	SHEET 1 OF 1